

◆引线加工规格 / LEAD CUTTING FORMING SPECIFICATIONS

SEACON provides lead-formed and lead-cut products to facilitate mounting on printed circuit boards, as well as products with leads specially processed (kink formed) for self supporting insertions to printed circuit boards.

• Lead forming

($\phi 5 \sim \phi 8$)

Lead forming code : FA

(mm)

ϕD	5	6.3	8
ϕd	0.5		0.6
F	5.0		

• Lead cutting

($\phi 10 \sim \phi 18$)

Lead cutting code : CA
CC
CE

(mm)

ϕD	10	12.5	14.5	16	18
H	5.0 (CA)				
	4.0 (CC)				
	3.5 (CE)				
ϕd	0.6		0.8		
F	5.0		7.5		

• Kinked lead forming

($\phi 5 \sim \phi 8$)

Kinked lead forming code : KC

• Kinked lead cutting

($\phi 10 \sim \phi 18$)

Kinked lead cutting code : KC

(mm)

ϕD	5	6.3	8	10	12.5	14.5	16	18
H1	4.5							
H2	2.8							
H3	2.5		—					
F	5.0				7.5			
P	1.0							
E	1.2			1.3				
ϕd	0.5		0.6			0.8		

V-CHIP
GENERAL PURPOSE
LOW PROFILE
LONG LIFE
LOW IMPEDANCE
LOW LEAKAGE CURRENT
BI-POLAR
FOR SWITCHING POWER SUPPLY
SNAP-IN TYPE
LUG TERMINAL TYPE
SCREW TERMINAL TYPE
PHOTO FLASH
HIGH RIPPLE FARAD

P.19